

User manual Airgo® Active Back Cushion / Comfort®


Congratulations!

You are now the owner of the Airgo® Active Back Cushion / Comfort, a product “made in Germany”. This tool was produced in compliance with valid EU norms. It is free of forbidden phthalates and heavy metals.

Important information for individual adaptation of your Airgo Active Back Cushion / Comfort before you use it for the first time.

The Airgo Active Back Cushion / Comfort is fitted with a needle valve and is shipped ex works inflated. Please check whether the level of inflation is just right for your personal needs and comfort. Using the TOGU® Ball Pump included with the product, you can regulate the internal pressure yourself quite simply:

- The inflation / deflation needle is recessed into the head of the Ball Pump handle (under the yellow, labelled dot)
- Open the zipper. The valve is located on the back of the product.
- To deflate the Airgo Active Back Cushion / Comfort, moisten the needle, insert it straight into the valve and press out excess air.
- To inflate the Airgo Active Back Cushion / Comfort, moisten the needle, insert it straight into the valve and pump in air.



The Airgo Active Back Cushion / Comfort is available in standard version with a clip and in comfort version with a velcro fastener.

Installation:


Installing the Airgo Active Back Cushion / Comfort on your car seat is done using the belt.

First open the clip/velcro fastener. The clip can be opened by pressing inwards on the two lateral tabs. Now lean the Airgo Active Back Cushion / Comfort with its flat back side (the side with the zipper) against the back of your car seat. Make sure that the shorter belt is pointing towards the seat and the longer towards the headrest.

Now pull the shorter belt down between the back of the seat and the seat and out through the back. The longer belt is passed between the headrest and the back of the seat. Then, the two belt sections can be connected with the clip/ velcro fastener at the back of your seat. To close the clip, push the two parts together until a clear „click“ is heard.

Please make sure the longer belt has the length adjustment feature. The comfort cushion can be changed in length by the velcro. This enables you to adapt the Airgo Active Back Cushion / Comfort to just about any car seat. Always make sure the Airgo Active Back Cushion / Comfort is connected tightly to your car seat.

You can now adjust the height of your Airgo Active Back Cushion / Comfort to suit your taste and achieve maximum sitting comfort.



Information:

If desired, you can also remove the cover of the Airgo Active Back Cushion / Comfort entirely. However, make sure you don't damage the cover while doing so, since it is fitted tightly to the Airgo Active Back Cushion / Comfort to avoid wrinkling.

Warning!

The Airgo Active Back Cushion / Comfort and the back of your car seat must be adjusted so that your shoulders contact the back of the seat. This ensures that the distance between your head and the headrest is correct. See the operating instructions for your car for detailed information on adjusting the seat and headrest.